the worker UI on a single web page. The timeline is shown with significant events indicated by a dot. The UI presents several extra details for demo purposes. Note points 1 through 5 in the interface. Point 1 is the indication of the deployment of the MPC smart contract with the addresses of the organizer and the worker initialized. Point 2 represents the worker collecting recyclable plastics in bins and getting them verified. Point 3 is the organizer (Account 1 in MetaMask for this demo) sending micropayments in response to the collection. Note that the worker-receiver address-account number is prepopulated (for this demo). Point 4 is the area where the micropayments will be displayed (again for demo purposes). Point 5 is the claim interaction with the MPC smart contract by the worker (Account 2 in MetaMask for this demo). Also, note the balances of the three accounts: the smart contract, the organizer, and the worker. The values are updated as you progress through the demo.

INTERACT WITH MPC-DAPP

Here are the steps to follow to simulate a complete micropayment channel interaction. You can follow along with these commands when you complete the deployment of the smart contract and the Node.js server per instructions given in section 7.4.7:

1. In MetaMask, reset Account 1 and Account 2 for initializing the nonce to the starting point. You reset the nonce of accounts by clicking the Account icon and then selecting Settings > Advanced Settings > Reset Account. You reload the UI web page when switching between organizer and worker roles.