- Ropsten network endpoint addresses for the project, saved in BAEnv.txt. (See section 8.4.4 for Ropsten endpoint on Infura.)
- Gather all these configurations in a BAEnv.txt file that contains the details given in listing 8.2. Download the template BAEnv.txt from this chapter's codebase, and prepare all the data required, as discussed in this section. All the missing data in the file should be filled with your setup details before you start the exploration of the blind auction Dapp.

NOTE The parameters in the environment can be set up in the .env file and accessed as a variable of the .env instance. That will introduce a layer of obscurity that is common in a production environment. For testing purposes, you'll use this ready reference in the xyzEnv.txt file that contains all the configurations details, such as the mnemonic and Infura endpoints. This file also contains argument values for interacting with the application.

Listing 8.2 BlindAuction configuration parameters (BAEnv.txt)

```
BIP39 mnemonic generation tool:
    https://iancoleman.io/bip39/#english

Beneficiary details:
    1. Mnemonic or seed phrase from BIP39 tool:

    2. Account address Account1 on Metamask:

    3. Infura project name: Role1

    4. Infura endpoint address for Ropsten:
    https://ropsten.infura.io/v3/......

Bidder1 Details:
    1. Mnemonic or seed phrase from BIP39 tool:

    2. Account address Account1 on MetaMask:

Bidder2 details:
    1. Mnemonic or seed phrase from BIP39 tool:
```