```
    2. Account address Account1 on MetaMask:

BlindAuction contract address on deployment of smart contract from
➥ Beneficiary:                                                          ❶
...

Keccak hash values for 1, 2 and 3: for bids                              ❷
1
0xeef3620c18bdc1beca6224de9c623311d384a20fc9e6e958d393e16b74214ebe
2
0x54e5698906dca642811eb2f3a357ebfdc587856bb3208f7bca6a502cadd7157a
3
0x74bbb8fdcb48d6f82df6e9067fd9633fff4cab1103f0d5cb8b4de7214cbdcea1
```

❶ This address is available on the deployment of the smart contract.

❷ Used in the calculation of hash for the bids

8.5.2 Decentralized participants

In the blind auction problem, the beneficiary and bidders are distinct participants with their own laptops or machines to configure and deploy the Dapp. But you're going to simulate all three roles on a single laptop by

- Switching the account in MetaMask every time you interact from a different role: beneficiary, bidder1, or bidder2.
- (Optional) Using different listening ports for the web server of the beneficiary and bidders--3000, 3010, 3020 for quick identification of the various roles when interacting. If you prefer, you can change the server port number in the index.js file along with the message that is displayed.

After you download the blind auction code and expand it, you'll see a graphical layout of the directory structure (figure 8.12). The figure shows the different roles that you identified