limited number of assets is possible if you consider all the real estate assets in an entire town or country, or the whole world. The standard is an interface that specifies functions (headers) that are required to be implemented. For a token to be ERC721-compliant, it has to implement the required functions of the ERC721 interface standard. The design of the ERC721 interface piggybacked on the ERC20 definition. The ERC721 standard is also evolving as I write this chapter. A new function called `safeTransferFrom()` has been added to the ERC721 interface, for example. Here are the functions of the ERC721 interface that are used in the development of RES4:

```
interface ERC721 {
function balanceOf(address _owner) external view returns (uint256 balance);
function ownerOf(uint256 _tokenId) external view returns (address owner);
function approve(address _to, uint256 _tokenId) external payable;
function transferFrom(address _from, address _to, uint256 _tokenId) external
➥ payable;
function safeTransferFrom(address _from, address _to, uint256 _tokenId)
➥ external payable;
...}
```

Besides these functions, we've also used a function from another standard ERC721-Enumerable interface: `function totalSupply() public view returns (uint256 total)`. The `totalSupply()` function limits the number of tokens. The number of items are limited for many assets, including paintings, art, and habitable land on earth. The next two functions, `balanceOf()` and `ownerOf()`, gives details on tokens (assets) owned by an address. The function `approve()` is required for ERC721 to allow an address to spend the token. But it is very important to note that in the RES4, with real estate as an asset, the approval has a different meaning: approval of an asset (token) for sale to a specific address. The functions `transferFrom()` and `safeTransferFrom()` are variations of functions to transfer an asset from one address to another.