Given these functions, how do you incorporate the ERC721 standard into your smart contract and Dapp development? That's what you'll learn next.

> **NOTE** ERC token standards are in flux, changing in numbering, support classes, and functions. This situation is understandable for an emerging subject such as tokenization. Some tokens are implemented as only partially compatible with the standards. Be aware of these aspects when you develop a token.

RES4 SMART CONTRACT

Using the use case diagram (figure 9.3) and the contract diagram (figure 9.4) as guidelines, develop the smart contract for RES4. Figure 9.5 shows the block diagram of the Dapp. Observe a new element: the ERC721 token interface. The RES4 smart contract will use the inheritance of traditional object-oriented design for involving ERC721, as shown in figure 9.5. You'll have to add ERC721 as another smart contract (ERC721.sol) in the contracts directory. It also needs other support contracts. These contracts are located in `helper_contracts` directory to separate them from the main RES4 contract. The ERC721 interface is incorporated into the code by the following additions to the smart contract. Follow these steps to inherit the features of one smart contract into another:

1. Import the ERC721 standard interface at the beginning of the smart contract code for RES4:

   ```
   import "./helper_contracts/ERC721.sol";
   ```

   The ERC721 smart contract is imported from a `helper_contracts` directory that also has other contracts used by ERC721.sol. Open the contracts directory, and browse the helper contracts. You'll find many support contracts.