```
    event Approval(address owner, address approved, uint256 tokenId);  ❸

    constructor()public {
        supervisor = msg.sender; }

// ERC721 functions                                                    ❹

    function balanceOf() public view returns (uint256) {... }

    function ownerOf(uint256 assetId) public view returns (address) {... }

    function transferFrom(address payable from, uint256 assetId)...{ ...}

    function approve(address to,uint256 assetId) public { ...}

    function getApproved(uint256 assetId) ... returns (address) { ...}


// Additional functions added for RES4 token                           ❺

    function addAsset(uint256 price,address to) public{ ... }

    function clearApproval(uint256 assetId,address approved) public {...}

    function build(uint256 assetId,uint256 value) public payable { ...}

    function appreciate(uint256 assetId,uint256 value) public{ ...}

    function depreciate(uint256 assetId,uint256 value) public{ ... }

    function getAssetsSize() public view returns(uint){...    }

// Functions used internally                                           ❻

    function mint(address to, uint256 assetId) internal { ...}

    function exists(uint256 assetId) internal view returns (bool) { ... }

    function isApprovedOrOwner(address spender, uint256 assetId) {...}

 // Other ERC721 functions for compliance }
```

❶ RES4 is an ERC721 token.
❷ Hash tables for managing tokens
❸ Events indexed and recorded on blocks
❹ ERC721 functions used by RES4
❺ RES4 Dapp-specific functions
❻ Internal functions

Follow the model provided by this ERC721-compliant smart contract, and use it as a guideline for implementing any other