NFT Dapp. You can reuse the ERC721-based code and add to your application-specific code to this base code.

TRANSFERFROM FUNCTION

The signature of the `transferFrom()` function implemented in RES4.sol is slightly different from the one defined in ERC721. It has two parameters--`from address` and `asset id`--instead of the three parameters of the same function of ERC721. In the RES4 case, the third parameter is implied and can be obtained from the `msg.sender`. Instead of a centralized authority or a designated person requesting the transfer, the approved person, or the account buying the asset, requests the transfer. In my opinion, this deviation is justifiable, as it (RES4 version of `transferFrom()`) implements a decentralized peer-to-peer transfer, with the blockchain acting as an intermediary.

9.2.5 Interaction with RES4 Dapp

The next step is developing the app part of the RES4 in the RES4-app module, which exposes its functions in a web UI. Download RES4-Dapp.zip, unzip it, and review the structure. You'll deploy it on the local Ganache test chain, where ten accounts with balances are readily available. Following the structure in figure 9.5, locate the various parts of the Dapp. Then run the following steps to explore the workings of the RES4 token:

1. Start the Ganache test chain by clicking Quickstart. Copy the mnemonics at the top of the Ganache GUI. Link MetaMask to Ganache, using the mnemonics copied from the Ganache interface.