```
it('Failure on bid in invalid state.', async function () { ...
}

  describe('REVEAL Phase.', async ()=>{
       it('Success on refund of difference when sent value is >
                                                                bid amount.',
    it('Success on refund when sent value is less than bid amount.',...{
    it('Success on refund if bid amount is less than highest bid.', ...{
    it('Failure on incorrect key for reveal.', async function () {
    it('Failure on incorrect bid value for reveal.', async function () {
    it('Failure on reveal in invalid state.', async function () {
... }

describe('Withdraw.', async ()=>{
    it('Success on withdraw on loosing bid.', async function () {
...}

describe('Auction end.', async ()=>{
it('Success on end of auction on single bid.', async function () {
it('Failure on end of auction in invalid phase.', async function () {
...}

describe('Full Auction Run.', async ()=>{
it('Success on run with 3 accounts.', async function () {
...}
```

Let’s examine the test script for the blind auction in listing 10.4. This test script has the usual `beforeEach()`, which allows the blind auction contract to be deployed before every test described by `describe()`. By now, the `describe-it` combination should be quite familiar to you from the examples of counter and ballot smart contracts. Each `describe()` function has many `it()` test cases, and each test case tests the success or failure of a certain condition. The aspect is described in the string message of the `it()` test, beginning with a `'Success on'` condition for a positive test and a `'Failure on...condition'` for a negative test. Five of the six tests in listing 10.4 defined by `describe()` are for testing the status of blind auction functions: