- Initialization and phase change
- Bidding phase
- Reveal phase
- Withdraw
- Auction end

Each `describe()` is further defined by several `it()`s based on the individual operations and the corresponding tests. A sixth `describe()` in listing 10.4 walks through the complete end-to-end operation of the blind auction.

There could be two more tests for the `withdraw()` function: one for the failure of the winner of the bid trying to withdraw, and one for failure of `withdraw()` from an incorrect state. These tests are left as exercises for you to try on your own.

10.5.1 Analysis of describe() and it() code

Download the *blindAuctionTest.js* from the codebase of this chapter, and examine its content. Let's examine one `it()` of the `describe()` for the bidding phase to understand how to define and code the `describe()` test:

```
describe('Bidding Phase.', async ()=>{
    it('Success on single bid.', async function () {
      // Before bidding
      let balanceBefore = Number(web3.utils.fromWei(await
                   (web3.eth.getBalance(ACC1), 'ether'));
      // Bidding
      let bidInWei = web3.utils.toWei(String(BID1), 'ether');
      let valueInWei = web3.utils.toWei(String(BID1+1), 'ether');
      let hashValue = web3.utils.keccak256(..);
      await blindAuction.bid(hashValue, {from: ACC1, value: valueInWei});
      // After bidding
```