```
npm install
truffle test
```

The output of the test run shows six sets of outputs resulting in 16 test cases: initialization and change phase, bidding, reveal, auction end, withdraw, and full auction run. Each of these test items is represented by `describe()`. Every `describe()` has a `beforEach()` setting up the tests and several `it()` tests. Every `describe()` has a meaningful string parameter that specifies the nature of the test, and that string is output as shown in figure 10.5, identifying the tests.

```
Contract: BlindAuction
  Initialization and Phase Change.
    ✓ Success on initialization to bidding phase.
    ✓ Success on phase change by beneficiary. (177ms)
    ✓ Success on change from DONE phase to INIT phase. (233ms)
    ✓ Failure on phase change by a non-beneficiary. (64ms)
  Bidding Phase.
    ✓ Success on single bid. (1049ms)
    ✓ Failure on bid in invalid state. (117ms)
  Reveal Phase.
    ✓ Success on refund of difference when sent value is greater than bid amount. (215ms)
    ✓ Success on refund when sent value is less than bid amount. (170ms)
    ✓ Success on refund if bid amount is less than highest bid. (297ms)
    ✓ Failure on incorrect key for reveal. (165ms)
    ✓ Failure on incorrect bid value for reveal. (171ms)
    ✓ Failure on reveal in invalid state. (108ms)
  Withdraw.
    ✓ Success on withdraw on loosing bid. (349ms)
  Auction end.
    ✓ Success on end of auction on single bid. (272ms)
    ✓ Failure of end of auction in invalid phase. (49ms)
  Full Auction Run.
    ✓ Success on simulated auction with 3 bidders (accounts). (754ms)


16 passing (6s)
```

Figure 10.5 Test output from blind auction testing

10.5.3 Full auction run