public deployment
MPC use case
setting up environment 215
setting up MPC environment 217

R
recoverSigner() function 175
regID (request identifier) 155
register() function 43, 49, 66, 69, 71-72, 74, 100, 152, 155, 157, 283
Remix JavaScript VM 101
replenish() function 157, 159
replenishEscrow() function 152, 155
reqID (request identifier) 157, 160
reqPhase parameter 65
Request for Comments (RFC) 16, 228
request() function 49-50
requests for proposals (RFPs) 127
require statement 65, 234, 265
require() function 55, 59, 65, 75-76
requires node modules 289
reqWinner() function 59, 69, 72, 74, 100
reset option 91
response() function 49-50
restricted sandbox environment 30
return statement 31
Reveal phase 119, 121-122, 125, 127, 134-135, 141-143, 212, 215, 264
reveal() function 122, 125, 143
RevealStarted event 134-135, 137, 144
revert() function 59, 65, 75, 278
RFC (Request for Comments) 16, 228
RFPs (requests for proposals) 127
RIPEMD160 function 110, 118
ropsten-infura endpoint 287
Ropsten-Infura Ethereum node 204

S
safeTransferFrom() function 235-236
SEC (Securities and Exchange Commission) 229
selfdestruct() function 192
selfdestruct(sender) function 177
settlePayment() function 49, 51, 152, 155, 160
Sha (secure hash) 180
SHA256 function 118
shh package 165
side channels 167
sign() function 180