```
"content":[
            {
               "type": "tool-call",
               "tool": "getWeatherReport",
               args: { city: 'Dublin' },
            }]
```

SYSTEM PROMPTS

System messages set the context or behavior for the entire conversation. They're typically used at the beginning of a chat session. You need to use the special `system` property that is available. Other reasons to use system messages may also include compliance, messaging, and creating personas:

```
generateText({
    prompt: 'Hello, how are you?',
    model: model("models/gemini-2.0-flash"),
    system: "I'm happy to assist you in any way I can.
How can I be of service today?"
});
```

Generally, when using the Vercel AI SDK, it's important to maintain a consistent approach to prompt types to create complex, interactive AI experiences. The SDK automatically transforms messages into a format wrapped with the appropriate control tokens, allowing developers to focus on crafting effective prompts and managing conversation flow.

5.1.3 Organizing your prompts: Versioning, testing, and optimization

We now explore strategies for prompt versioning, testing, and optimization, providing practical examples to illustrate each approach.

PROMPT MANAGEMENT

Prompt management is important when you want to programmatically handle prompts or store them in a database outside your version control system. This is mainly done for the following reasons:

- *Dynamic updates*—Storing prompts in a database allows you to update them without redeploying your application. This is crucial for fine-tuning prompts based on user feedback or performance metrics.
- *Version control*—A database can easily store multiple versions of the same prompt, allowing you to A/B test different prompt variations or roll back to previous versions if needed.
- *Scalability*—As your application grows, you might need to manage hundreds or thousands of prompts. A database provides better scalability and querying capabilities than storing prompts in code.
- *Access control*—With a database, you can implement role-based access control, allowing different team members (e.g., prompt engineers, data scientists) to modify prompts without touching the application code.