functions, we can chain multiple AI calls together. This allows us to combine the results of these individual calls to achieve more complex outcomes.

In the next chapter, we'll explore a library called LangChain, which is designed to simplify the process of chaining AI calls and makes it more powerful. For now, it's important that you understand just the basic concepts and building blocks of prompt management.

PROMPT VERSIONING

In terms of keeping track of prompts as you modify them during the development of the application you are building, you should consider a few things. First, depending on the AI model changes, you will need to keep track of the different versions of prompts to track changes, improvements, and the effects of those changes on the output generated.

Say, for example, you are developing a generative AI web app for content creation for a health blog. You start with a basic prompt:

```
Version 1: "Write a blog post about the benefits of working out."
```

As you gather user feedback and analyze the output, you might notice that the posts lack depth. You decide to refine the prompt:

```
Version 2: "Write a detailed blog post about the benefits of working out,
including scientific studies, personal anecdotes, and practical tips."
```

Those are clearly different versions, so how do you keep track of their effectiveness on the specific AI provider? Here are some practical options:

- *Using a version control system*—Use Git or another version control system to track changes in your prompt files. This would work sufficiently for tracking the difference in wording but not so much when comparing the overall performance of their difference.
- *Using semantic versioning*—A slightly better way is to apply semantic versioning to your prompts, especially for critical ones. This includes crafting a naming scheme that you can use to store the prompts based on their current version or the model that they should apply. Here is an example:

```
// prompts/translation_openai_v1.0.1.ts
export const translationPrompt_openai_v1_0_1 =
"Translate the following text from {source_lang}
to {target_lang}: {text}";
// prompts/translation_openai_v1.1.0.ts
export const translationPrompt_openai_v1_1_0 =
"You are a professional translator. Translate the
following text from {source_lang} to {target_lang},
maintaining the original tone and style: {text}";

// prompts/translation_anthropic_v1.0.0.ts
```