```
  prompt: "Write a poem about love.",
  maxTokens: 100, // Limit response to 100 tokens
});
```

Imposing a `maxTokens` value lets you control the size of the generated responses, which could allow you to pack more conversations within a context window without losing valuable information.

- *Rolling conversation context*—With rolling context, we send only a limited number of past messages (e.g., the last 10), so you can ensure that your application stays within token limits while still providing relevant context:

```
while (messageHistory.length > 10) {
  messageHistory.shift(); // Remove the oldest message
}
```

Pairing the token limit with the `maxTokens` parameter enables you to calculate the length of the `messageHistory` allowed for each conversation thread. By selecting a round number that is divisible by the provider's token limits, you can ensure that your application operates within the boundaries.

- *Token count monitoring*—You can implement a monitoring mechanism to track the total number of tokens being used in your conversation history. To achieve this, you can utilize libraries like js-tiktoken, which allows you to encode messages and calculate their token counts accurately. However, it's important to note that js-tiktoken may not support all AI models, so you might need to develop a custom solution for those that are not covered.

Even when you have abstractions to measure the number of tokens you send with each request, your application might get an influx of incoming responses that would fail. For that use case, you want to have an option to perform retries. However, it's important to understand that retries should primarily be for transient errors (e.g., network glitches, temporary service unavailability, or rate limiting) and generally not for persistent problems like exceeding your API quota. The following section explains how to configure this option.

RETRYING FAILED REQUESTS

The `maxRetries` parameter from each of `streamText`, `generateText`, `streamUI`, and the related family of functions allows you to specify the maximum number of times a request should be retried if it fails due to transient errors, such as rate limiting or server problems.

While it may seem counterintuitive to retry a Too Many Requests (HTTP 429) error, this type of error is indeed retryable, because rate limits are typically temporary and time-based. A 429 indicates that you've exceeded a request threshold within a brief window; it's not a permanent block. For example, you can set `maxRetries` when making API calls: