```
const response = await streamText({
  model: supportedModel,
  prompt: "Generate a summary of the latest news.",
  maxRetries: 3, // Retry up to 3 times on failure
});
```

In this case, if the request fails due to a retryable error (like a 429), the SDK will automatically attempt to resend the request up to the specified number of retries before ultimately failing.

If the LLM provider is down or unavailable, you can also consider using a fallback model.

MODEL FALLBACKS

A package like the ai-fallback library is a good candidate that offers model fallbacks. This library provides a structured way to implement model fallback mechanisms when interacting with AI models. Specifically, if an AI provider becomes unavailable, the fallback mechanism will automatically trigger and reroute the request to an alternative provider. Here's how to set it up:

1. Install the ai-fallback library. Add the npm package to your project dependencies list:

   ```
   $ npm install ai-fallback
   ```

2. Create a fallback model. You can create a fallback model that will automatically switch between different AI providers when errors occur, such as hitting token limits or experiencing rate limiting. In our example, we just use Open AI, with Google AI as a fallback.

Listing 8.3 Creating a fallback model

```
import { createFallback } from 'ai-fallback';
import { createOpenAI } from '@ai-sdk/openai';
import { createGoogleGenerativeAI } from '@ai-sdk/google';

const openAPIKey = process.env.OPENAI_API_KEY;
const googleAPIKey = process.env.GEMINI_API_KEY;

// Create a fallback model instance
const supportedModel = createFallback({
  models: [
    createGoogleGenerativeAI(
{ apiKey: googleAPIKey })('models/gemini-2.0-flash'),
    createOpenAI({ apiKey: openAPIKey })('gpt-3.5-turbo'),
  ],
  onError: (error, modelId) => {
    console.error(`Error with model ${modelId}:`, error);
  },
  modelResetInterval: 60000,
});
```

Imports the createFallback function from the ai-fallback library to create a fallback model for AI interactions

Creates an instance of a fallback model that can switch between different AI models

Sets the interval (in milliseconds) for resetting back to the primary model after an error occurs