```
            text: `You can use the get-chuck-joke
or get-chuck-joke-category tools to fetch jokes.
Here is a joke to summarize:\n"${joke}"`
          }
        }
      ]
    };
  }
);
```

This prompt constructs a user message instructing the AI to summarize a joke. The joke itself can be retrieved using the `get-chuck-joke` tool, and the AI generates the concise summary in response.

DEFINING A RESOURCE

Resources provide static or preloaded context that clients or AI models can access directly. This could be a file, a JSON object, or any kind of text.

Listing 12.6 Adding a resource to the Chuck Norris MCP server

```
server.resource(
  'examples',
  'examples://chuck-norris',
  async (uri) => ({
    contents: [{
      uri: uri.href,
      text: `
# Chuck Norris MCP Server Examples  ...
`
    }]
  })
);
```

Registers a new resource with the server

Provides a URI so clients and the AI can request this resource

Defines the actual content returned when the resource is read

This resource contains a Markdown document describing the Chuck Norris MCP server examples, including which tools and prompts are available. It can be used by clients or the AI for reference or context.

RUNNING THE MCP INSPECTOR

The MCP Inspector is the interface for exploring and interacting with resources registered on the Chuck Norris MCP server. To run the inspector for this example, use the following command as mentioned in the sidebar "MCP resources and project code: `mcp`":

```
$ npm run dev -w ch12/mcp
```

The inspector will automatically instantiate the script mcp.js and open a new browser window. It is particularly useful for debugging, testing, and experimenting with the server in real time. Figure 12.6 shows the view of the inspector when we use `get-chuck-joke`.