how long the calling thread will be blocked, only that if the function returns `false`, then `Clock::now()` returns a time equal to or later than `absolute_time` at the point at which the thread became unblocked.

Throws

Any exception thrown by a call to `pred`, or `std::system_error` if the effects couldn't be achieved.

Synchronization

Calls to `notify_one()`, `notify_all()`, `wait()`, `wait_until()`, and `wait_until()` on a single `std::condition_variable_any` instance are serialized. A call to `notify_one()` or `notify_all()` will only wake threads that started waiting *prior* to that call.

D.3. <atomic> header

The `<atomic>` header provides the set of basic atomic types and operations on those types and a class template for constructing an atomic version of a user-defined type that meets certain criteria.

Header contents

```
#define ATOMIC_BOOL_LOCK_FREE  see description
#define ATOMIC_CHAR_LOCK_FREE  see description
#define ATOMIC_SHORT_LOCK_FREE  see description
#define ATOMIC_INT_LOCK_FREE  see description
#define ATOMIC_LONG_LOCK_FREE  see description
#define ATOMIC_LLONG_LOCK_FREE  see description
#define ATOMIC_CHAR16_T_LOCK_FREE  see description
#define ATOMIC_CHAR32_T_LOCK_FREE  see description
#define ATOMIC_WCHAR_T_LOCK_FREE  see description
#define ATOMIC_POINTER_LOCK_FREE  see description
```