```
    void store(integral-type,memory_order = memory_order_seq_cst)
         volatile noexcept;
    void store(integral-type, memory_order = memory_order_seq_cst)
noexcept;
    integral-type load(memory_order = memory_order_seq_cst)
         const volatile noexcept;
    integral-type  load(memory_order = memory_order_seq_cst) const
noexcept;
    integral-type  exchange(
        integral-type, memory_order = memory_order_seq_cst)
         volatile noexcept;
    integral-type  exchange(
        integral-type,memory_order = memory_order_seq_cst)
noexcept;

    bool compare_exchange_strong(
        integral-type & old_value,integral-type  new_value,
         memory_order order = memory_order_seq_cst) volatile
noexcept;
    bool compare_exchange_strong(
        integral-type & old_value,integral-type  new_value,
          memory_order order = memory_order_seq_cst) noexcept;
    bool compare_exchange_strong(
        integral-type & old_value,integral-type  new_value,
         memory_order success_order,memory_order failure_order)
         volatile noexcept;
    bool compare_exchange_strong(
        integral-type & old_value,integral-type  new_value,
         memory_order success_order,memory_order failure_order)
noexcept;
    bool compare_exchange_weak(
        integral-type & old_value,integral-type  new_value,
          memory_order order = memory_order_seq_cst) volatile
noexcept;
    bool compare_exchange_weak(
        integral-type & old_value,integral-type  new_value,
          memory_order order = memory_order_seq_cst) noexcept;
    bool compare_exchange_weak(
        integral-type & old_value,integral-type  new_value,
         memory_order success_order,memory_order failure_order)
         volatile noexcept;
    bool compare_exchange_weak(
        integral-type & old_value,integral-type  new_value,
         memory_order success_order,memory_order failure_order)
noexcept;
    operator integral-type () const volatile noexcept;
    operator integral-type() const noexcept;

    integral-type  fetch_add(
        integral-type, memory_order = memory_order_seq_cst)
```