```
         volatile noexcept;
    integral-type  fetch_add(
        integral-type, memory_order = memory_order_seq_cst)
noexcept;
    integral-type  fetch_sub(
        integral-type, memory_order = memory_order_seq_cst)
         volatile noexcept;
    integral-type  fetch_sub(
        integral-type, memory_order = memory_order_seq_cst)
noexcept;
    integral-type  fetch_and(
        integral-type, memory_order = memory_order_seq_cst)
         volatile noexcept;
    integral-type  fetch_and(
        integral-type, memory_order = memory_order_seq_cst)
noexcept;
    integral-type  fetch_or(
        integral-type, memory_order = memory_order_seq_cst)
         volatile noexcept;
    integral-type  fetch_or(
        integral-type, memory_order = memory_order_seq_cst)
noexcept;
    integral-type  fetch_xor(
        integral-type, memory_order = memory_order_seq_cst)
         volatile noexcept;
    integral-type  fetch_xor(
        integral-type, memory_order = memory_order_seq_cst)
noexcept;

    integral-type  operator++() volatile noexcept;
    integral-type  operator++() noexcept;
    integral-type  operator++(int) volatile noexcept;
    integral-type  operator++(int) noexcept;
    integral-type  operator--() volatile noexcept;
    integral-type  operator--() noexcept;
    integral-type  operator--(int) volatile noexcept;
    integral-type  operator--(int) noexcept;

    integral-type operator+=(integral-type ) volatile noexcept;
    integral-type operator+=(integral-type ) noexcept;
    integral-type operator-=(integral-type ) volatile noexcept;
    integral-type operator-=(integral-type ) noexcept;
    integral-type operator&=(integral-type ) volatile noexcept;
    integral-type operator&=(integral-type ) noexcept;
    integral-type operator|=(integral-type ) volatile noexcept;
    integral-type operator|=(integral-type ) noexcept;
    integral-type operator^=(integral-type ) volatile noexcept;
    integral-type operator^=(integral-type ) noexcept;
};
```