```
bool atomic_is_lock_free(volatile const atomic<integral-type >*)
noexcept;
bool atomic_is_lock_free(const atomic<integral-type >*) noexcept;
void atomic_init(volatile atomic<integral-type>*,integral-type )
noexcept;
void atomic_init(atomic<integral-type>*,integral-type ) noexcept;
integral-type  atomic_exchange(
    volatile atomic<integral-type>*,integral-type) noexcept;
integral-type  atomic_exchange(
    atomic<integral-type>*,integral-type) noexcept;
integral-type  atomic_exchange_explicit(
    volatile atomic<integral-type>*,integral-type , memory_order)
noexcept;
integral-type  atomic_exchange_explicit(
    atomic<integral-type>*,integral-type , memory_order) noexcept;
void atomic_store(volatile atomic<integral-type>*,integral-type)
noexcept;
void atomic_store(atomic<integral-type>*,integral-type) noexcept;
void atomic_store_explicit(
    volatile atomic<integral-type>*,integral-type , memory_order)
noexcept;
void atomic_store_explicit(
    atomic<integral-type>*,integral-type , memory_order) noexcept;
integral-type atomic_load(volatile const atomic<integral-type >*)
noexcept;
integral-type atomic_load(const atomic<integral-type >*) noexcept;
integral-type  atomic_load_explicit(
    volatile const atomic<integral-type >*,memory_order) noexcept;
integral-type  atomic_load_explicit(
    const atomic<integral-type>*,memory_order) noexcept;
bool atomic_compare_exchange_strong(
    volatile atomic<integral-type>*,
    integral-type * old_value,integral-type  new_value) noexcept;
bool atomic_compare_exchange_strong(
    atomic<integral-type>*,
    integral-type * old_value,integral-type  new_value) noexcept;
bool atomic_compare_exchange_strong_explicit(
    volatile atomic<integral-type>*,
    integral-type * old_value,integral-type  new_value,
    memory_order success_order,memory_order failure_order)
noexcept;
bool atomic_compare_exchange_strong_explicit(
    atomic<integral-type>*,
    integral-type * old_value,integral-type  new_value,
     memory_order success_order,memory_order failure_order)
noexcept;
bool atomic_compare_exchange_weak(
    volatile atomic<integral-type>*,
    integral-type * old_value,integral-type  new_value) noexcept;
bool atomic_compare_exchange_weak(
```