- A standard Frequent Flyer member only earns the base point value of a trip.
- A Silver Frequent Flyer will earn a 50% status bonus.
- A Gold Frequent Flyer will earn a 75% status bonus.
- A Gold Frequent Flyer also benefits from a guaranteed minimum of 1,000 points per trip.

You could write examples illustrating these rules as separate scenarios, as shown in the following listing.

Listing 5.1 Scenarios for calculating bonus points based on Frequent Flyer status

```
Feature: Earning extra points from Frequent Flyer status

  Scenario: A standard Frequent Flyer earns the base point value of a trip
    Given I am a Standard Frequent Flyer member
    When I fly on a flight that is worth 439 base points
    Then I should earn a total of 439 points

  Scenario: A Silver Frequent Flyer will earn a 50% status bonus
    Given I am a Silver Frequent Flyer member
    When I fly on a flight that is worth 439 base points
    Then I should earn a status bonus of 220 points
    And I should earn a total of 659 points

  Scenario: A Gold Frequent Flyer will earn a 75% status bonus
    Given I am a Gold Frequent Flyer member
    When I fly on a flight that is worth 2040 base points
    Then I should earn a status bonus of 1530 points
    And I should earn a total of 3570 points

  Scenario: A Gold Frequent Flyer benefits from a guaranteed minimum of 1000
    points per trip
    Given I am a Gold Frequent Flyer member
    When I fly on a flight that is worth 439 base points
    Then I should have a guaranteed minimum of 1000 earned points per trip
    And I should earn a total of 1000 points
```

This is starting to get quite wordy. Having a lot of similar scenarios to describe a set of related business rules is a poor practice; the duplication makes the scenarios harder to maintain. In addition, after the first couple of almost-identical scenarios, readers are likely to just skim over the subsequent ones and miss important details, making them a poor communication tool.

When you're writing scenarios in BDD, a good rule of thumb is "less is more." You can often describe behavior more concisely and more effectively using a single scenario and a table of examples that summarizes the different cases. For example, you could express these examples more succinctly in JBehave like this:

Express the rule in more generic terms. Data from the example table is passed into the steps.

```
Scenario: Earning extra points on flights by Frequent Flyer status
Given I am a <status> Frequent Flyer member
When I fly on a flight that is worth <base> base points
Then I should earn a status bonus of <bonus>
And I should have guaranteed minimum earned points per trip of <minimum>
And I should earn <total> points in all
```