```
Examples:
| status   | base | bonus | minimum | total |
| Standard | 439  | 0     | 0       | 439   |
| Silver   | 439  | 220   | 0       | 659   |
| Gold     | 439  | 329   | 1000    | 1000  |
| Gold     | 2040 | 1530  | 1000    | 3570  |
```

The scenario will be checked for each row of data in the table.

Summarize the different cases using a few well-chosen examples.

This is effectively four scenarios wrapped into one—the scenario will be run four times, each time with the values from one row in the example table. Data from the table is passed into each step via the field names in angle brackets: `<status>`, `<base>`, and so forth. You've reduced four wordy scenarios into a single concise scenario and a table of examples!

Another advantage of a concise format like this is that it's easier to spot missing examples that might need clarification and to add extra examples. In the examples we've discussed so far, you've included the guaranteed minimum points for Gold Frequent Flyers but not for Silver Frequent Flyers. Paul tells you that Silver Frequent Flyers are guaranteed to earn at least 500 points per trip. To make this clear, you can add another example to your table. You can also add a `notes` column, which isn't used in the scenario but lets you annotate the examples with a little extra detail:

```
Scenario: Earning extra points on flights by Frequent Flyer status
  Given I am a <status> Frequent Flyer member
  When I fly on a flight that is worth <base> base points
  Then I should earn a status bonus of <bonus>
  And I should have guaranteed minimum earned points per trip of <minimum>
  And I should earn <total> points in all
Examples:
  | status   | base | bonus | minimum | total | notes
  | Standard | 439  | 0     | 0       | 439   |
  | Silver   | 148  | 74    | 500     | 500   | minimum points
  | Silver   | 439  | 220   | 500     | 659   | 50% bonus
  | Gold     | 439  | 329   | 1000    | 1000  | minimum points
  | Gold     | 2041 | 1531  | 1000    | 3572  | 75% bonus
```

In Gherkin, the format is similar, but you use the `Scenario Outline` keyword:

```
Scenario Outline: Earning points on flights by Frequent Flyer status
    Given I am a <status> Frequent Flyer member
    When I fly on a flight that is worth <base> base points
    Then I should earn a status bonus of <bonus>
    And I should have guaranteed minimum earned points of <minimum>
    And I should earn <total> points in all
Examples:
    | status   | base | bonus | minimum | total |
    | Standard | 439  | 0     | 0       | 439   |
    | Silver   | 148  | 74    | 500     | 500   |
    | Silver   | 439  | 220   | 500     | 659   |
    | Gold     | 439  | 329   | 1000    | 1000  |
    | Gold     | 2041 | 1531  | 1000    | 3572  |
```

Scenario Outline keyword marks this as a table-driven scenario.

Test data used for this scenario.

When you use a table of sample data like this, the scenario will be checked once for each row in the table, making this the equivalent of five separate scenarios. But presenting