```
public enum Status {Gold, Silver, Bronze};

@Given("I am a (.*) Frequent Flyer member")
public void useAMemberWithAGivenStatus(Status status) {
    ...
}
```

This use of regular expressions is typical of most of the Cucumber-based tools. Regular expressions are extremely powerful and allow a great deal of flexibility in how you express your step definitions. But they can be intimidating for developers who aren't used to them. Some tools, such as JBehave and SpecFlow, propose simpler (and often more readable) alternatives to regular expressions. For example, in JBehave you can use variable names instead of regular expressions, as shown here:

```
@Given("I am a $status Frequent Flyer member")
public void useAMemberWithAGivenStatus(Status status) {
    ...
}
```

This style gains in readability, at the cost of a certain loss of flexibility.

6.2.4 Maintaining state between steps

A scenario contains several steps, and sometimes you'll need to pass information from one step to another. The simplest way to do this is to use member variables within the class or script containing the step definitions. A new instance of the step definitions will be created for each new scenario execution, so there's no chance of the values being overwritten.

The following code illustrates this principle. Suppose you're implementing the following scenario:

```
Scenario: Earning extra points on flights based on frequent flyer status
  Given I am a Silver Frequent Flyer member
  When I fly from Sydney to Melbourne on 01/01/2013 at 09:00
  Then I should earn 439 points
```

To do this, you need to create or retrieve a Frequent Flyer member object in the first step and an object corresponding to the requested trip in the second, and then use both of these objects to calculate how many points this member would earn for this trip. The corresponding step definition class using JBehave might look like this:

```
public class EarningPointsSteps {
    TripSteps trips;
    Members members;

    FrequentFlyerMember member;
    Trip trip;

    @Given("I am a $status Frequent Flyer member")
    public void defineAMemberWithStatus(String status) {
        member = members.getMember().withStatus(status);
    }
```

Application-specific libraries.

Domain objects used to store state between steps.

Find or create a member with a given status.