You could then reuse this data in subsequent steps, like this:

```
@When("$name books a flight")
public void booksFlight(String name) {
    Member member = Thucydides.getCurrentSession().get("member")
    ...
}
```

Reuse the member you stored earlier.

6.4.4 Passing tables to steps

As you've seen, JBehave provides the `ExamplesTable` class to handle embedded tables in your scenarios. In JBehave, these parameters are known as *tabular parameters*. Suppose you need to automate the following scenario step:

```
Given I have travelled on the following flights:
  | flight | from      | to        | date       |
  | FH-603 | Sydney    | Cairns    | 01-05-2012 |
  | FH-604 | Cairns    | Sydney    | 05-05-2012 |
  | FH-603 | Sydney    | Melbourne | 01-07-2012 |
  | FH-604 | Melbourne | Sydney    | 02-07-2012 |
  | FH-603 | Sydney    | Brisbane  | 28-07-2012 |
  | FH-604 | Brisbane  | Sydney    | 02-08-2012 |
```

You could implement a step in JBehave using an `ExamplesTable` parameter like this:

A date formatter used to parse the date column.

Pass the table as an ExamplesTable.

Iterate over the rows in the table.

Extract field values from the row.

Update the test database with the new data.

```
SimpleDateFormat formatter = new SimpleDateFormat("dd-MM-yyyy");

@Given("I have travelled on the following flights: $flights")
public void travelled_on_flights(ExamplesTable flights)
  throws ParseException {
    for(Map<String,String> flightDetails : flights.getRows()) {
        Flight flight = Flight.number(flightDetails.get("flight"))
              .from(flightDetails.get("from"))
              .to(flightDetails.get("to"));

        Date date = formatter.parse(flightDetails.get("date"));
        member.flewOnFlight(flight).on(date);
    }
}
```

This is a very basic use of the `ExamplesTable` class, but it does reflect typical usage of tabular parameters.

6.4.5 Step definitions for tables of examples

Another very powerful use of tables, which you saw in section 5.3.2, is to summarize a number of similar scenarios into a single scenario with a table of examples, as shown here:

```
Scenario: Earning extra points on flights by Frequent Flyer status
  Given I am a <status> Frequent Flyer member
  When I fly on a flight that is worth <base> base points
  Then I should earn a status bonus of <bonus>
  And I should have guaranteed minimum earned points per trip of <minimum>
  And I should earn <total> points in all
```