```
@When("I fly from $departure to $destination")
@Alias("I travel from <departure> to <destination>")
public void whenIFlyFrom(String departure,
                         String destination) {
    // TODO: add this flight to the member's account
}
```

If the variations are very close, you can also use the more compact format shown here:

```
@When("I {fly|travel} from $departure to $destination on $date at $time")
public void whenIFlyFrom(String departure,
                         String destination,
                         DateTime date,
                         LocalTime time) {
    // TODO: add this flight to the member's account
}
```

These approaches give more flexibility in writing the scenarios, and streamline implementing the step definitions, because there's no need to write duplicate methods or normalize the scenario texts unnecessarily.

6.4.7 Failures and errors in the scenario outcomes

As with all BDD tools, JBehave reports on successful, failing, and pending steps. But when used with Thucydides, JBehave also distinguishes between failures (the application doesn't produce the expected outcome) and errors (the application, or possibly the scenario itself, throws an unexpected exception). A failure generally indicates an application bug, whereas an error may indicate a scenario that's broken or that no longer reflects the correct behavior of the application. For example, you saw this scenario earlier:

```
Scenario: Earning standard points from an Economy flight
Given the flying distance between Sydney and Melbourne is 878 km
And I am a standard Frequent Flyer member
When I fly from Sydney to Melbourne on 01/01/2013 at 09:00
Then I should earn 439 points
```

You could implement the last step of this scenario using the following step definition:

```
@Then("I should earn $points points")
public void thenIShouldEarn(int points) {
    assertThat(points).isEqualTo(earnedPoints);
}
```

Did you earn the right number of points?

The earnedPoints variable is assigned in a previous step. ❶

Here you're checking that the calculated number of points is what you expected ❶. If the number of points earned isn't 439, this step will fail, which will cause the scenario as a whole to fail.

But failures are not always this simple. In figure 6.6, the third step has failed with the error message, "Frequent Flyer account not activated." This isn't an expected exception, and it could come either from an application bug or incorrect test logic.