Cucumber-JS enjoys a large developer community, and it's easy to set up and use. It also integrates well with other tools in the JavaScript ecosystem. For example, if you're writing an AngularJS application using the Karma test runner, you can use the Cucumber/Karma integration package (https://npmjs.org/package/karma-cucumberjs) to test your AngularJS code directly using Cucumber. At the time of writing, this tool is still under active development, and not all of its features are mature or available, but it's an active project with frequent updates.[12]

6.9 Summary

In this chapter, you learned about automating scenarios:

- To automate a scenario, you write *step definitions* using the BDD tool of your choice.
- Step definition methods interpret the step text and call the appropriate methods to manipulate the application under test.
- JBehave is a well-documented Java-based BDD tool with tight Thucydides integration.
- Cucumber-JVM provides a Gherkin implementation for JVM-based languages.
- Behave is a Gherkin implementation for Python.
- SpecFlow is a Gherkin implementation for .NET with tight Visual Studio integration.
- Cucumber-JS is one of several BDD implementations in JavaScript.

You should now have a good idea of how to automate your acceptance criteria using the language and framework of your choice. But automating scenarios is only the first step—you also need to get these automated scenarios to actually test your application. In the next chapter, you'll learn how to turn these automated scenarios into effective, expressive, and maintainable automated acceptance tests.

[12] The Cucumber-JS web page (https://github.com/cucumber/cucumber-js) has a table summarizing the current status of feature implementation.