Although it has no equivalent to JBehave's `@BeforeStory` and `@BeforeStories` annotations, Cucumber does provide a feature that native JBehave lacks.[2] The preceding method will be called before each and every scenario in the test suite, whether it uses the database or not. This is clearly not ideal, especially if only a small part of your acceptance criteria are end-to-end acceptance criteria. Cucumber provides for a more selective approach, where you specify an annotation to indicate which scenarios this hook should apply to:

```
Feature: Joining the Frequent Flyer Program

@end-to-end
Scenario: Registering online for a new Frequent Flyer account
...
```

Flag this scenario as an end-to-end scenario.

You can then refer to this tag in the `@Before` annotation, causing Cucumber to only call this method for scenarios with the `@end-to-end` tag:

```
@Before("@end-to-end")
public void initializeDatabase() {
    TestDatabase.initialize();
}
```

Only call this method before scenarios flagged with the @end-to-end tag.

In this way, Cucumber-JVM provides an elegant way of resetting your test database only when you really need to do so.

Initialization hooks in Behave

Behave, the Python BDD tool introduced in chapter 6, also provides a rich set of hook methods that you can define in the `environment.py` module. These methods are intuitively named:

- `before_scenario` and `after_scenario`
- `before_feature` and `after_feature`
- `before_tag` and `after_tag`
- `before_all` and `after_all`

To reset the test database before each scenario, you might do something like this:

```
def before_scenario(context, scenario):
    context.database.reset()
```

If you needed to reset the database uniquely for end-to-end scenarios, you could check for the presence of the `@end-to-end` tag, as shown here:

```
def before_scenario(context, scenario):
    if 'end-to-end' in scenario.tags:
        context.database.reset()
```

Initialization hooks in SpecFlow

SpecFlow has a particularly broad set of hooks, including `BeforeTestRun`, `BeforeFeature`, and `BeforeScenario`. Like Cucumber-JVM, it allows you to optionally specify

[2] The Thucydides extension for JBehave does provide support for this feature.