a tag that indicates the scenarios where you would like a method executed. For example, the code to reset the database before each end-to-end scenario might look something like this:

```
[BeforeScenario("end-to-end")]
public static void BeforeEndToEndScenario()
{
    InitializeTestDatabase();
}
```

You've now seen how you could place the test database into a clean state before each scenario. Now let's consider how to inject specific data for each scenario.

7.2.4 Setting up scenario-specific data

When you create a new database, you'll usually want to populate it with (at least) reference data and possibly some sample production-like data. But even with a fresh database for each new scenario, it's not a good idea to rely too heavily on prepopulated data. Scenarios should be self-explanatory, and if you rely on predefined test data, it can make it harder to know what the test is actually doing. For example, the following scenario uses a prepopulated set of timetables:

```
Scenario: Tell users about the next departure times from a given station
Given I want to travel from Parramatta to Town Hall at 8:00
When I ask about the next trains to depart
Then I should be told about the trains at: 8:02, 8:11, 8:14
```

This scenario assumes not only that project team members and stakeholders know about the geographical locations of Parramatta and Town Hall stations (this isn't an unreasonable expectation for people working in the Sydney public transport network—see figure 7.6), but also that they know the times of trains that are scheduled to arrive at Town Hall. This is less obvious, and as a result, the intent of the scenario is unclear. Why these trains and not others? What trains should *not* be included?

Some data, such as the names of the stations and the lines that connect them, would be well known to stakeholders. You can safely populate the initial test database with this sort of reference data; putting it into the scenario would just add clutter and distract from the more essential information. But details that are likely to change often, or that are central to the business rule you're trying to illustrate, should be included in the scenario.

A better way to express this scenario might be as follows:

Specify the business rule being described. ❶

```
Scenario: Tell users about the next departure times from a given station
We should show the next three departing trains
Given Western Line trains get to Parramatta at 7:58,8:02,8:08,8:11,8.14
When I want to travel from Parramatta to Town Hall at 8:00
Then I should be told about the trains at: 8:02, 8:08, 8:11
```

The Western Line is well known to business stakeholders and users. ❷

❸ **Specify which trains should be included in the results.**