Table 8.2 Useful CSS selectors *(continued)*

Selector	Example	Notes
`[attribute=value]`	`a[href="#/book"]`	Matches `<a>` elements with an `href` value of `#/book`
`[attribute^=value]`	`a[href^="#"]`	Matches `<a>` elements with an `href` value that starts with `#`
`[attribute$=value]`	`a[href$="book"]`	Matches `<a>` elements with an `href` value that ends in `book`
`[attribute*=value]`	`a[href*="book"]`	Matches `<a>` elements with an `href` value that contains `book`
`:nth-child(n)`	`.navbar li:nth-child(3)`	Matches the third `<li>` inside an element of class `navbar`

Let's look at a more practical example. One of the requirements you've defined with the marketing folk goes along the following lines:

```
Scenario: Displaying featured destinations
Given Jane has logged on
When Jane views the home page
Then she should see 3 featured destinations
And the featured destinations should include Singapore
```

On the Frequent Flyer home page, each featured destination appears inside a `<div>` element with the `featured` class. The destination title is nested inside a `<span>` element with the `featured-destination` class. The rendered HTML code looks something like this:

```
<div id="featured">
    <div class="featured-destination"...>
        <img src="img/singapore.png"></img>
        <span class="destination-title">Singapore</span>
        <span class="destination-price">$900</span>
    </div>
    <div class="featured-destination">...</div>
    <div class="featured-destination">...</div>
</div>
```

All the featured destinations appear within this .

Each featured destination has its own .

Set the featured destination's title.

Set the featured destination's image.

Other featured destinations like this follow.

In CSS, you can match elements with a given class by using the period (`.`) prefix. Using a CSS selector, you could find all of the `<div>` elements that represent the featured destinations like this:

```
List<WebElement> destinations
    = driver.findElements(By.cssSelector(".featured-destination"));
assertThat(destinations).hasSize(3);
```

1. **Find all the featured destination elements.**
2. **Check the number of matching featured destination elements.**