you can use XPath expressions to select arbitrary elements within the HTML page structure. A list of useful XPath expressions can be found in table 8.3.

Table 8.3 Useful XPath expressions

XPath expression	Example	Notes
`node`	`a`	Matches all of the `<a>` elements
`//node`	`//button`	Matches all of the `<button>` elements somewhere under the document root
`//node/node`	`//button/span`	Matches `<span>` elements that are situated directly under a `<button>` element
`[@attribute=value]`	`//a[@class='navbar-brand']`	Matches `<a>` elements whose `class` attribute is exactly equal to `navbar-brand`
`[contains(@attribute, value)]`	`//div[contains(@class, 'navbar-header')]`	Matches `<div>` elements whose `class` attribute contains the expression `navbar-header`
`node[n]`	`//div[@id='main-navbar']//li[3]`	Matches the third `<li>` inside the `<div>` with an `id` of `main-navbar`
`[.=value]`	`//h2[.='Flying High Frequent Flyers']`	Matches the `<h2>` element with text contents equal to `Flying High Frequent Flyers`

You can find an element via an XPath expression by using the `By.xpath()` method. You could find the welcome message heading by using the following expression:

```
driver.findElement(By.xpath("//h3[@id='welcome-message']"));
```

XPath requires more knowledge of the document structure than CSS, and it doesn't benefit from the intimate understanding of HTML that's built into CSS selectors. This makes simple selectors more verbose than their equivalents in CSS. For example, in the previous section you saw how you could find the list of featured destination titles using the following CSS selector:

```
driver.findElements(By.cssSelector(".destination-title"));
```

The equivalent in XPath might be something like this:

```
driver.findElements(By.xpath("//span[@class='destination-title']"));
```