```
When Joe applies for a Flying High Credit Card
Then Joe should be informed that Flying High will be in touch
And Joe's application should be queued for manual processing
```

Both of these scenarios illustrate key paths through the application and focus on how the user interacts with the website. You could implement them using the approaches we discussed in chapter 8.

However, because these acceptance criteria focus on the user experience and high-level outcomes, they deliberately gloss over some important underlying business logic. In particular, how do you determine if Joe is eligible or not? And depending on the scope of the feature, you may also need to explore other questions. How will the feature attract new Frequent Flyer members, and how will it earn revenue for the organization? This may involve some complex business rules. If you were to write automated web tests for each of these rules, it would slow down and add complexity to the test suite without adding a great deal of reporting value.

For example, income is an important consideration. The Flying High sales manager explains that regular Frequent Flyers with an annual income of over $120,000 will be approved automatically, whereas those with an income less than $50,000 will be declined. Those in between will need to be processed manually:

```
Scenario Outline: Credit card eligibility based on income
Given Joe is a regular Frequent Flyer earning <income>
When Joe applies for a Flying High Credit Card
Then his application should be <result>
Example:
income | result         | notes
120000 | automatic      | Income >= 120000
100000 | manual         |
49999  | declined       | Income < 50000
```

But Frequent Flyer status also influences eligibility. Depending on a member's status, their application may be accepted automatically, even with a lower income:

```
Scenario Outline: Credit card eligibility based on income and status
Given Joe is a <status> Frequent Flyer earning <income>
When Joe applies for a Flying High Credit Card
Then his application should be <result>
Example:
status | income | result     | notes
gold   | 80000  | automatic  | Automatically approved over $80000
gold   | 79999  | manual     |
gold   | 49999  | declined   |
silver | 100000 | automatic  | Automatically approved over $100000
silver | 99999  | manual     |
bronze | 110000 | automatic  | Automatically approved over $110000
bronze | 109999 | manual     |
```

As you can see here, table-based scenarios are a great way to explore business rules, and they can be used to discuss and illustrate both positive and negative scenarios.