retrieve the current flight status from the model (most likely via a service layer), and prepare the flight status screen with the corresponding status information.

Cucumber-JVM provides excellent integration with Spring and Spring MVC. You could automate this scenario using Cucumber in Java with the following code:

```
@WebAppConfiguration
@ContextConfiguration("classpath:cucumber.xml")
public class FlightStatusSteps {

    @Autowired
    private FlightStatusService flightStatusService;

    @Autowired
    private MockMvc mockMvc;

    private String flightId;
    private ResultActions resultActions;

    @Given("^that flight (.*) has no reported delays$")
    public void no_reported_delays_for_flight(String flightId)
      throws Throwable {
        this.flightId = flightId;
        flightStatusService.updateStatusForFlight(flightId)
                           .to(FlightStatus.ON_TIME);
    }

    @When("^I check the flight status$")
    public void I_check_the_flight_status() throws Throwable {
        resultActions = mockMvc.perform(get("/flights/{flightId}",
                                            flightId))
                               .andExpect(status().isOk());
    }

    @Then("^I should see that it is (.*)$")
    public void I_should_see_that_it_is(FlightStatus expectedStatus)
      throws Throwable {
        resultActions.andExpect(view().name("flightstatus"))
                .andExpect(model().attribute("flightId",
                           is(flightId)))
                .andExpect(model().attribute("flightStatus",
                           is(expectedStatus.toString())));
    }

    @Then("^I should see its scheduled arrival time of (.*)$")
    public void expect_scheduled_arrival_time_of(String arrivalTime)
      throws Throwable {
        resultActions.andExpect(model().attribute("eta",
                                is(arrivalTime)));
    }
}
```



In this test you use Spring to configure the components and services it needs to retrieve the flight status ❶ and set up the test data using an existing service class ❷. Next, you invoke the flight status controller with the `flightId` parameter ❹ and check that the controller retrieved the expected values ❹ and ❺ and that you're redirected to the right screen ❸.