WHAT SHOULD THE APPLICATION DO NEXT?

When your unit test (or, more precisely, your executable specification) passes, you need to decide what test to write next. In BDD terms, you ask, "What should the application do that it doesn't already do in order to satisfy the acceptance criteria I'm working on?" The acceptance criteria remind you of what you're trying to achieve and help you avoid being sidetracked.

In this case, with the preceding builder implemented, there's little left to explore in the area of creating new Frequent Flyer members, so you can safely move on to the last step in the acceptance criterion, which checks the status of the Frequent Flyer member. You could implement this step definition as shown here:

```
@Then("^(?:s?)he should have a status of (.*)$")
public void should_have_status_of(Status expectedStatus) {
    assertThat(member.getStatus()).isEqualTo(expectedStatus);
}
```

The Status class represents the concept of member status levels.

You need to be able to get a member's status.

Writing this step definition leads to the discovery of a new domain class (the `Status` class) and a new method to obtain the status of a member. This requirement would probably be simple enough to implement directly from the step definition, but you could also choose to write a more focused unit test to illustrate the initial member status:

```
@Test
public void the_members_initial_status_should_be_bronze() {
    FrequentFlyer member
        = FrequentFlyer.withFrequentFlyerNumber("123456789")
                                    .named("Jill", "Smith");

    assertThat(member.getStatus()).isEqualTo(Status.Bronze);
}
```

Create a Frequent Flyer member.

The initial status should be Bronze.

The implementation for this should be simple. You could implement member status as an enumerated type, like the following:

```
public enum Status { Bronze, Silver, Gold, Platinum; }
```

Then you'd simply add a status attribute and a getter method to the `FrequentFlyer` class:

```
public class FrequentFlyer {

    private String frequentFlyerNumber;
    private String firstName;
    private String lastName;
    private Status status = Status.Bronze;
    ...
    public Status getStatus() {
        return status;
    }
}
```