```
    member.earns(150).statusPoints();
    assertThat(member.getStatusPoints()).isEqualTo(250);
}
```

When Joe earns 150 points...

Then he should have a total of 250 points.

This is still pretty simple code. The final step in the acceptance criterion is the interesting part, where you check the business logic around status points and status levels:

```
Then he should have a status of <finalStatus>
```

You've already implemented the step definition for this step:

```
@Then("^(?:s?)he should have a status of (.*)$")
public void should_have_status_of(Status expectedStatus) {
    assertThat(member.getStatus()).isEqualTo(expectedStatus);
}
```

But this is where things get a little more interesting. The acceptance criterion will still not pass, which indicates that the implementation is incomplete. When a member earns additional status points, their status should also be updated if enough points have been accumulated.

You could express this in more technical terms by writing the following unit test:

When a new Frequent Flyer member...

```
@Test
public void should_obtain_a_new_status_when_enough_points_are_earned() {
    FrequentFlyer member
                    = FrequentFlyer.withFrequentFlyerNumber("12345678")
                                   .named("Joe", "Bloggs");
        member.setStatusPoints(100);
        member.earns(200).statusPoints();
        assertThat(member.getStatus()).isEqualTo(Status.Silver);
}
```

With 100 status points...

Earns 200 status points...

Then the member should get Silver status.

This is a low-level example of how the application code updates member status. Note that you've just expressed one of the examples from the acceptance criterion as a unit test. Although this unit test is a little redundant (after all, it tests exactly the same thing as one of the examples in the acceptance criterion), it's still useful, because it acts as the starting point for implementing the status upgrade functionality. It also concisely documents how this piece of functionality is implemented.

10.3.2 Working with tables of examples

Many acceptance criteria use example tables to summarize a number of related scenarios, as you saw in this scenario:

```
Scenario Outline:
  Given Joe Jones is a <initialStatus> Frequent Flyer member
  And he has <initialStatusPoints> status points
  When he earns <extraPoints> status points
  Then he should have a status of <finalStatus>
```

Describe how the application should behave.