10.5.2 Fluent assertions in JavaScript

JavaScript has a number of libraries that can help make your assertions more expressive. You've seen, for example, the built-in `expect()` method that comes with Jasmine:

```
expect(frequentFlyer.getStatus()).toBe('Silver');
```

But this sort of expressiveness isn't limited to Jasmine. Should.js (https://github.com/visionmedia/should.js/) and Chai (http://chaijs.com) are other well-known libraries that support similar features.

Chai is probably the most flexible of these, supporting both the "expect" and "should" formats, as well as the old-school assert. Chai focuses on using method chaining to make the assertions fluid and readable. For example, the Chai equivalent of the Jasmine `expect` statement would be the following:

```
var expect = require('chai').expect
...
expect(frequentFlyer.getStatus()).to.equal('Silver');
```

Import the Chai expect function.

Expect assertions are similar to those in Jasmine.

As you might expect, Chai supports a rich collection of assertions and can chain multiple assertions together. For example,

```
var obtainableStatuses = ['Silver','Gold','Platinum']
...
expect(obtainableStatuses).to.have.length(3).and.to.include('Gold')
```

Chai also supports the more BDD-style `should` assertion, as illustrated here:

```
var expect = require('chai').should();

frequentFlyer.getStatus().should.equal('Bronze');

obtainableStatuses.should.have.length(3).and.include('Silver');
```

Note that you're calling the should() function, not importing it.

Should can now be called on any object.

All the assertion methods can be called using either expect or should.

Both styles are equally expressive, so the choice is largely a question of style and personal preference.

10.5.3 Fluent assertions in static languages

Fluent assertion libraries also exist for static languages such as Java and .NET, although they're generally a bit less expressive than their dynamic equivalents.

Java, for example, has several fluent assertion libraries. The two best known are Hamcrest (https://github.com/hamcrest/JavaHamcrest) and FEST-Assert (https://github.com/alexruiz/fest-assert-2.x/wiki). More recent versions of NUnit come with a similar constraint-based assert model, and .NET developers can also use the very rich Fluent Assertions library (https://github.com/dennisdoomen/FluentAssertions).