```
Given Western line trains from Emu Plains leave Parramatta
for Town Hall at 7:58, 8:00, 8:02, 8:11, 8:14, 8:21
When I want to travel from Parramatta to Town Hall at 8:00
Then I should be told about the trains at: 8:02, 8:11, 8:14
```

Identifies six train times to make the example more representative.

Now you expect to obtain three results.

Before we take this example any further, or move on to more complicated requirements, let's see how you can transform these acceptance criteria into executable specifications, using JBehave, Maven, and Git in this chapter.

2.4.2 Setting up Maven and Git

There are many specialized BDD tools that you can use to automate your acceptance criteria. Popular choices include tools like JBehave, Cucumber, SpecFlow, and Behat. While not indispensable, these tools make it easier to express the automated tests in a structured form similar to the "Given ... When ... Then" expressions used in the previous section. This makes it easier for product owners and testers to understand and identify the automated acceptance criteria, which in turn can help increase their confidence in the automated tests and in the automated acceptance-testing approach in general.

Throughout the rest of this book, I'll illustrate examples using several different BDD tools. In this chapter, I'll use examples written with JBehave and Java,[5] and the project will be built and run using Maven.[6] The test reports will be generated using Thucydides,[7] an open source library that makes it easier to organize and report on BDD test results.

The source code for this chapter is available on GitHub[8] and on the Manning website. If you want to follow along, you'll need a development environment with the following software installed:

- A Java JDK (the sample code was developed using Java 1.7.0, but it should work fine with JDK 1.6.0)
- Maven 3.0.x
- Git

GitHub lets you access a repository in a number of ways. If you have Git installed and a GitHub account set up with SSH access,[9] you can clone the sample code repository like this:

```
$ git clone git@github.com:bdd-in-action/chapter-2.git
```

If you haven't set up and configured SSH keys for GitHub, you can also use the following command (Git will ask you for your username and password):

```
$ git clone https://github.com:bdd-in-action/chapter-2.git
```

---

[5] If Java isn't your cup of tea, don't worry; the code samples are designed to be readable by anyone with some programming background. We'll look at BDD tools in .NET, Ruby, and Python from chapter 5 onwards.

[6] Maven (http://maven.apache.org/) is a widely used build tool in the Java world.

[7] See the Thucydides site (http://thucydides.info) for more details about this library.

[8] The source for this chapter on GitHub is at https://github.com/bdd-in-action/chapter-2.

[9] See GitHub help (https://help.github.com/articles/set-up-git) for a good tutorial on installing Git for your OS.