You'll start with the first scenario we looked at in listing 2.1:

```
Scenario: Find the optimal itinerary between stations on the same line
Given Western line trains from Emu Plains leave Parramatta for Town Hall at
7:58, 8:00, 8:02, 8:11, 8:14, 8:21
When I want to travel from Parramatta to Town Hall at 8:00
Then I should be told about the trains at: 8:02, 8:11, 8:14
```

Continuing this example using JBehave and Java, you could implement an empty automated test for this scenario in a class called `OptimalItinerarySteps.java` as shown in the next listing.

Listing 2.4 A pending JBehave scenario implementation

```
package com.bddinaction.chapter2.jbehave.steps;

import org.jbehave.core.annotations.Given;
import org.jbehave.core.annotations.Pending;
import org.jbehave.core.annotations.Then;
import org.jbehave.core.annotations.When;
import java.util.List;
import org.joda.time.LocalTime;

public class OptimalItinerarySteps {
    @Given("$line line trains from $lineStart leave $departure for
            $destination at $departureTimes")
    @Pending
    public void givenArrivingTrains(String line,
                                    String lineStart,
                                    String departure,
                                    String destination,
                                    List<LocalTime> departureTimes) {
    }

    @When("I want to travel from $departure to $destination at $time")
    @Pending
    public void whenIWantToTravel(String departure,
                                  String destination,
                                  LocalTime time) {
    }

    @Then("I should be told about the trains at: $viableTrainTimes")
    @Pending
    public void shouldFindTheseTrains(List<LocalTime> viableTrainTimes) {
    }
}
```

❶ A Given step

❷ Flag this step as pending

❸ A When step

❹ A Then step

This class goes in the steps package underneath the jbehave package in the src/test/java directory (see figure 2.7). JBehave tests can be implemented in Java or in other JVM languages such as Groovy or Scala. When it executes a scenario, JBehave will use the text from the `@Given` ❶, `@When` ❸, and `@Then` ❹ annotations to determine what method to call at each step. As the listing shows, you can also pass elements from the scenario text to the test methods in the form of parameters.