Data can include any text strings, bracketed by double quotes (“ and ”), and values or variables that include `char`, `byte`, `int`, `long`, or `string` data types. Any numerical value sent to the `print()` function will be converted to a text string. For integer values, a base can optionally be specified as either `BIN` for binary or base 2, `DEC` for decimal or base 10, `HEX` for hexadecimal or base 16, or `OCT` for octal or base 8. For a simple character string like in our example sketch, we used the following statement:

```
lcd.print("All I want");
```

This statement prints the text `All I want` beginning with the current cursor position and proceeding one character at a time to the right (by default) of that position. To send an integer value, we might write a line like the following:

```
lcd.print(analogRead(A0), DEC);
```

By combining the `analogRead()` function, this statement will read the value of the analog in pin A0 and print that value to the LCD in decimal format. Because the `print()` function will keep on spitting out characters to the right of the current position each time the function is called, we need to use some additional functions to control the position of the cursor.

clear()

The `clear()` function will clear all of the contents of the display and position the cursor in the top left of the display. There’s not much to the functions syntax because there are no values to pass to it, so let’s look at the following example of the function as used in our code:

```
lcd.clear();
```

Like I said, not much to it. Because of the way LCDs display data, this function can be useful for clearing the screen in order to write new data to it without overwriting data or sending data off the edge of the LCD.

setCursor()

When we want to move the position of the cursor on the display without clearing the display, we can use the `setCursor()` function to position the cursor anywhere on the display. Its syntax looks like the following:

```
setCursor(col, row)
```

All we need to do with this function is provide a number between 0 and 15 for the horizontal column position and either 0 or 1 for our two-row display. A position of `0,0` for example would be the top left corner of the display and `15,1` would be the last character on the bottom-right corner. The following is a line from our example code:

```
lcd.setCursor(0,1);
```

This line is used to set the cursor to the beginning or left-hand side of the second row of the display before writing the second line of text. In our haiku sketch, we used the `clear()` function to not only clear the display, but to also return the cursor to the top left of the display so `setCursor(0,0)` was not needed.