```
          height: '487', #G
          width: '640', #H
          videoId: 'm8IEpBuXKjk', #I
          events: {
            onReady: (event) => #J
              event.target.playVideo(),
          },
          playerVars: { #K
            autoplay: 1,
            mute: 1,
          },
        });
      }
    };
    return () => { #L
      delete window.onYouTubeIframeAPIReady;
    };
  }, []); #M
  return (
    <div>
      <h1>YouTube API Demo</h1>
      <div ref={playerRef}></div> #N
    </div>
  );
};
```

Although the code worked at runtime, TypeScript raised several errors:

- Property 'onYouTubeIframeAPIReady' does not exist on type 'Window'.
- Property 'YT' does not exist on type 'Window'.
- Parameter 'event' implicitly has an 'any' type.

**Analysis:** The interviewer used this scenario to assess Jane’s understanding of TypeScript’s static type system, global type augmentation, and best practices for integrating third-party JavaScript APIs.

**Jane’s Approach:** She explained that these errors arise because TypeScript’s static type checking requires all properties accessed on the global window object to be explicitly declared. The YouTube API, when loaded asynchronously, adds properties such as `YT` and `onYouTubeIframeAPIReady` to the global window object. However, TypeScript does not know about these properties by default, so it flags them as type errors.