Listing 2.3 Example index.css File

```
.title {
  font-size: 3em;
}
```

Inline styles should be limited to simple, dynamic cases, as they mix content with presentation and lack advanced CSS features. Preloading critical stylesheets and using responsive design techniques further help ensure efficient, scalable, and user-friendly styling in React applications.

Starting with React 19, developers can leverage the precedence attribute in `<link>` elements to control the priority of stylesheet loading. This feature enhances performance and reduces layout shifts, resulting in a smoother user experience. Demonstrating knowledge of this feature can also impress interviewers and highlight your familiarity with modern best practices.

Listing 2.4 preloadings stylesheets for the `BlogPost` Component, commented out in `components/blog-post/BlogPost.tsx`.

Listing 2.4 Preloading Stylesheets for the BlogPost Component

```
<link rel="stylesheet" href=
  "https://www.w3.org/Style/CSS/w3c-2010/main" precedence="defaul
<link rel="stylesheet" href=
  "https://www.w3.org/Style/CSS/twocolumn-print" precedence="high
```

In this example, the first stylesheet (main) uses a precedence of "default", while the second (twocolumn-print) uses "high". React automatically hoists these `<link>` tags to the `<head>` section of the document. Although React does not interpret the meaning of the precedence string, stylesheets with the same precedence value are grouped together in the order they are added. Notably, each stylesheet is loaded only once, even if it is referenced multiple times.

To observe the effects of precedence on rendering, try rearranging or uncommenting these `<link>` elements in `blog-post/BlogPost.tsx`. The result, shown in figure 2.4, uses the stylesheet from https://www.w3.org/Style/CSS/w3c-2010/main while running the command