For older browsers, the Clipboard API may not be available. In such cases, the deprecated but widely supported `document.execCommand('copy')` method can serve as a fallback. This approach involves creating a temporary textarea or input element, setting its value to the desired text, selecting its contents, and then executing the copy command. After the operation is complete, remove the temporary element from the DOM.

User interaction is a key requirement for clipboard operations—most browsers mandate that clipboard actions be triggered by a user gesture, such as clicking a button or using a keyboard shortcut, to prevent malicious or unexpected clipboard access. This means programmatic clipboard access cannot typically occur automatically or in the background; it must be in response to a user-initiated event, which helps protect user privacy and security. For example, a copy-to-clipboard function should be tied to a button click, and paste actions should respond to user input events.

Mobile devices may impose character limits (e.g., 20,000 characters on some Android devices) or limit the number of items stored in the clipboard. Inform users if their content is too large to copy, and consider splitting data if necessary.

Additionally, error handling is needed to manage scenarios where permissions are denied or the API is unsupported. By following these practices and understanding the importance of user-triggered actions, developers can create secure, user-friendly clipboard features that enhance interactivity and usability in web applications.

For this topic, are you able to answer these follow-up/probing questions?

- "Can you describe a scenario where you might want to use both clipboard read and write operations?"
- "How would you detect browser support for clipboard operations, and what fallback mechanisms might you implement?"
- "How do you handle situations where a user denies clipboard permissions?"
- "What considerations would you make for mobile browsers or devices with limited clipboard support?"
- "Why is clipboard access restricted to user-triggered events?"