Input	Output	Result
50	25	Perfect.
135	20	Over the sweet spot range of 0–100 CLOC results in a lower score.
18	25	Under 50 CLOC but by getting the absolute value it still yields 25.
450	0	An input of 450 results in -15, which is then normalized to 0.

Normalizing estimate health

As you saw earlier, estimate health was a 0 if everything was good, and as the value became larger or smaller than 0, it was getting worse. To normalize this, the team had to get the absolute value, compare the result to 0, and determine what the maximum tolerance was for over- or underestimating. If the absolute value was greater than 0, it should count against the total maximum value of 25. The team decided that if they were over- or underestimating by more than three days, then there was a big problem. They made the multiplier 7, which would bring the value really close to 0 if they were over or under by three days. For anything more than that, they made the value 0, as shown in this formula:

```
MAX((25 – (ABS(Estimate Health)* 7)), 0)
```

Example inputs and outputs are shown in table 7.3.

Table 7.3. Example inputs and outputs for normalizing estimate health data

Input	Output	Result
0	25	Perfect score; estimates are right on track.
1	18	Even a day will have a significant effect on the total.
-1	18	Because we take the absolute value, -1 and 1 have the same result.
3	4	At this point it’s guaranteed the total rating will be under 80.
4	0	Anything greater than 3 results in 0.

Normalizing recidivism

Recidivism results in a percentage or a decimal. The team was striving to keep tasks moving forward in their workflow so they wanted to have a low