- You can create simple metrics from single data points, or you can use formulas and algorithms to combine data for more complex and insightful metrics.
- Some example metrics used in this chapter:
    - ***Recidivism*** —Backward Tasks / (Forward Tasks + Backward Tasks)
    - ***Comment To Commit Ratio*** —code reviews / (merged pull requests + commits)
    - ***MTTR*** —Problem Fixed Time – Problem Identification Time
    - ***Continuous Release Quality Rating (CHD)*** —(25 - ABS((int) (cloc/50)-1) * 5) + (25-ABS(Estimate Health) * 7) + (Recidivism = 25 – ((bN / (fN + bN)) *50)) + (25 – (Escaped Defects * 10))
- Start off by taking time to explore your data to understand how it represents your team and how they work.
    - Use the data you have already to define what in your development cycle is good and worth repeating.
- Once you have a good understanding of your data, start combining data points to create metrics to track what matters most to your development cycle.
- Mind mapping is great way to get to the root of what to measure.
- Using the result of your mind map, create the formula to generate custom metrics.
- Adding live data into your formula gives you metrics that you can track in your development cycle.
- When changing your process, looking for new ways to measure your team is a key to success.
- Different teams within the same company can use similar ratings made up of different components as long as they’re measuring the same conceptual things.