Listing 3.13 Running ngrok (following the instructions setup)

```
./ngrok authtoken <YOUR_AUTHTOKEN>      #1
./ngrok http 8000      #2
```

#1 Enter your auth token obtained from ngrok.com.
#2 Opens a tunnel on port 8000 to external internet traffic

After you run ngrok, you'll see an external URL that you can now use to access the service on your machine. Copy this URL for later use when setting up the assistant. In the next section, we'll create the assistant that consumes this service as a custom action.

3.3.2 Connecting the custom action to an assistant

With the service up and running on your machine and accessible externally via the ngrok tunnel, we can build the new assistant. This time, we'll create a simple assistant to help us organize our daily tasks, where the tasks will be accessible from our locally running task service.

Open the GPT interface and the Configure panel, and copy and paste the instructions shown in listing 3.14 into the new assistant. Be sure to name the assistant and enter a helpful description as well. Also, turn on the Code Interpreter capability to allow the assistant to create the final plot, showing the tasks.

Listing 3.14 Task Organizer (`task_organizer_assistant.txt`)

```
Task Organizer is designed to help the user prioritize their daily tasks
based on urgency and time availability, providing structured guidance on
how to categorize tasks by urgency and suggesting optimal time blocks for
completing these tasks. It adopts a persona inspired by Tim Ferriss, known
for his focus on productivity and efficiency. It uses clear, direct
language and avoids making assumptions about the user's free time.
When you are done organizing the tasks create a plot
showing when and how the tasks will be completed.      #1
```

#1 This feature requires the Code Interpreter to be enabled.

Click the Create New Action button at the bottom of the panel. Figure 3.8 shows the interface for adding a custom action. You must copy and paste the OpenAPI specification for your service into the window. Then, you must add a new section called `servers` and populate that with your URL, as shown in the figure.