After you’re satisfied, everything is set. Refresh your browser window to reset the session, and enter something like the prompt shown in listing 3.15. This will prompt the agent to call the service to get your daily tasks, summarize the output, and solve your task organization dilemma.

Listing 3.15 Task Organizer prompt

```
how should I organize my tasks for today?
```

The assistant should produce a plot of the task schedule at the end. If it gets this wrong or the formatting isn’t what you prefer, you can add instructions to specify the format/style the assistant should output.

You can improve the service, but if you make any changes to the API, the specification in the assistant custom actions will need to be updated. From here, though, you can add custom action services run from your computer or hosted as a service.

> **Note** Be aware that unknown users can activate custom actions if you publish an assistant for public consumption, so don’t expose services that charge you a service fee or access private information unless that is your intention. Likewise, services opened through an ngrok tunnel will be exposed through the assistant, which may be of concern. Please be careful when publishing agents that consume custom actions.

Custom actions are a great way to add dynamic functionality to an assistant, whether for personal or commercial use. File uploads are a better option for providing an assistant with static knowledge. The next section will explore using file uploads to extend an assistant’s knowledge.

3.4 Extending an assistant’s knowledge using file uploads

If you’ve engaged with LLMs, you likely have heard about the retrieval augmented generation (RAG) pattern. Chapter 8 will explore RAG in detail for the application of both knowledge and memory. Detailed knowledge of RAG isn’t required to use the file upload capability, but if you need some foundation, check out that chapter.