Listing 4.12 `crewai_introduction.py` (task section)

```
research_task = Task(         #1
    description=(
        "Identify what makes the following topic:{topic} so funny."
        "Be sure to include the key elements that make it humourous."
        "Also, provide an analysis of the current social trends,"
        "and how it impacts the perception of humor."
    ),
    expected_output="A comprehensive 3 paragraphs long report
↪     on the latest jokes.",               #2
    agent=joke_researcher,      #3
)

write_task = Task(   #4
    description=(
        "Compose an insightful, humourous and socially aware joke on {topic}."
        "Be sure to include the key elements that make it funny and"
        "relevant to the current social trends."
    ),
    expected_output="A joke on {topic}.",   #5
    agent=joke_writer,        #3
    async_execution=False,          #6
    output_file="the_best_joke.md",      #7
)
```

#1 The Task description defines how the agent will complete the task.
#2 Explicitly defines the expected output from performing the task
#3 The agent assigned to work on the task
#4 The Task description defines how the agent will complete the task.
#5 Explicitly defines the expected output from performing the task
#6 If the agent should execute asynchronously
#7 Any output the agent will generate

Now, we can see how everything comes together as the `Crew` at the bottom of the file, as shown in listing 4.13. Again, many options can be set when building the `Crew`, including the agents, tasks, process type, memory, cache, maximum requests per minute (`max_rpm`), and whether the crew shares.