Listing 5.11 `Recommend_Movies/config.json`

```
{
    "schema": 1,
    "type": "completion",     #1
    "description": "A function to recommend movies based on users list of
previously seen movies.",
    "completion": {     #2
        "max_tokens": 256,
        "temperature": 0,
        "top_p": 0,
        "presence_penalty": 0,
        "frequency_penalty": 0
    },
    "input": {
        "parameters": [
            {
                "name": "input",     #3
                "description": "The users list of previously seen movies.",
                "defaultValue": ""
            }
        ]
    },
    "default_backends": []
}
```

#1 Semantic functions are functions of type completion.
#2 We can also set the completion parameters for how the function is called.
#3 Defines the parameters input into the semantic function

Next, we can look at the definition of the semantic function prompt, as shown in listing 5.12. The format is a little different, but what we see here matches the earlier examples using templating. This prompt recommends movies based on a list of movies the user has previously seen.

Listing 5.12 `Recommend_Movies/skprompt.txt`

```
You are a wise movie recommender and you have been asked to recommend a
movie to a user.
You are provided a list of movies that the user has watched before.
You want to recommend a movie that the user has not watched before.
[INPUT]
{{$input}}
[END INPUT]
```

Now, we'll dive into the code that loads the skill/plugin and executes it in a simple example. Open the `SK_first_skill.py` file in VS Code. The following listing shows an abridged version highlighting the new sections.