6.2.3 Installing the assistants database

To run several of the examples in this chapter, you'll need to install the assistants database. Fortunately, this can be easily done through the interface and just by asking agents. The upcoming instructions detail the process for installing the assistants and are taken directly from the GPT Assistants Playground README. You can install several of the demo assistants located in the `assistants.db` SQLite database:

1. Create a new assistant, or use an existing assistant.
2. Give the assistant the `create_manager_assistant` action (found under the Actions section).
3. Ask the assistant to create the manager assistant (i.e., "please create the manager assistant"), and be sure to name the assistant "Manager Assistant."
4. Refresh your browser to reload the assistants selector.
5. Select the new Manager Assistant. This assistant has the instructions and actions that will allow it to install assistants from the `assistants.db` database.
6. Talk to the Manager Assistant to give you a list of assistants to install, or just ask the Manager Assistant to install all available assistants.

6.2.4 Getting an assistant to run code locally

Getting agents and assistants to generate and run executable code has a lot of power. Unlike the Code Interpreter, running code locally provides numerous opportunities to iterate and tune quickly. We saw this earlier with AutoGen, where the agents could keep running the code until it worked as expected.

In the Playground, it's a simple matter to select the custom action `run_code`, as shown in figure 6.5. You'll also want to choose the `run_shell_command` action because it allows the assistant to `pip install` any required modules.