tool for diagnostics, but it also provides additional insights into the functions of LLMs.

We haven’t reviewed the code to do all this because it’s extensive and will likely undergo several changes. That being said, if you plan on working with the Assistants API, this project is a good place to start. With the Playground introduced, we can continue our journey into ABTs in the next section.

6.3 Introducing agentic behavior trees

Agentic behavior trees (ABTs) implement behavior trees on assistant and agent systems. The key difference between regular behavior trees and ABTs is that they use prompts to direct actions and conditions. Because prompts may return a high occurrence of random results, we could also name these trees *stochastic* behavior trees, which do exist. For simplicity, we’ll differentiate behavior trees used to control agents, referring to them as agentic.

Next, we’ll undertake an exercise to create an ABT. The finished tree will be written in Python but will require the setup and configuration of various assistants. We’ll cover how to manage assistants using the assistants themselves.

6.3.1 Managing assistants with assistants

Fortunately, the Playground can help us quickly manage and create the assistants. We’ll first install the Manager Assistant, followed by installing the predefined assistants. let’s get started with installing the Manager Assistant using the following steps:

1. Open Playground in your browser, and create a new simple assistant or use an existing assistant. If you need a new assistant, create it and then select it.
2. With the assistant selected, open the Actions accordion, and select the `create_ manager_assistant` action. You don’t need to save; the interface will update the assistant automatically.