6.3.3 Conversational AI systems vs. other methods

We already looked at conversational multi-agent systems in chapter 4 when we looked at AutoGen. The ABT can work using a combination of conversations (over threads) and other methods, such as file sharing. Having your assistants/agents pass files around helps reduce the number of noisy and repetitive thoughts/conversations. In contrast, conversational systems benefit from potential emergent behaviors. So, using both can help evolve better control and solutions.

The simple solution in listing 6.7 could be extended to handle more real-world coding challenges and perhaps even to work as a coding ABT. In the next section, we build a different ABT to handle a different problem.

6.3.4 Posting YouTube videos to X

In this section's exercise, we look at an ABT that can do the following:

1. Search for videos on YouTube for a given topic and return the latest videos.
2. Download the transcripts for all the videos your search provided.
3. Summarize the transcripts.
4. Review the summarized transcripts and select a video to write an X (formerly Twitter) post about.
5. Write an exciting and engaging post about the video, ensuring it's less than 280 characters.
6. Review the post and then post it on X.

Figure 6.9 shows the ABT assembled with each of the different assistants. In this exercise, we use a sequence node for the root, and each assistant performs a different action. Also, to keep things simple, each assistant interaction will always occur in a new thread. This isolates each assistant's interaction into a concise conversation that's easier to debug if something goes wrong.